

SHORAI CURVE White



- › Perfect aesthetics & new functionality in the HIGH LINE class
- › High efficiency: energy class A+++ / Clean air: Dust filter & plasma ionizer
- › App control: WiFi module integrated as standard
- › Transparent power consumption: Energy monitoring for single and multi-split systems
- › Definable SILENT function makes submission of official documents & deployment easier



SHORAI
Curve

INDOOR UNIT OUTDOOR UNIT			RAS-B10P2KVS-G-E RAS-10P2AVS-G-E	RAS-B13P2KVS-G-E RAS-13P2AVS-G-E	RAS-B16P2KVS-G-E RAS-16P2AVS-G-E	RAS-B18P2KVS-G-E RAS-18P2AVS-G-E	RAS-B22P2KVS-G-E RAS-22P2AVS-G-E	RAS-B24P2KVS-G-E RAS-24P2AVS-G-E
Cooling capacity	kW	❄️	2,50	3,50	4,60	5,00	6,10	7,00
Cooling range (min.-max.)	kW	❄️	0,89 - 3,20	1,00 - 4,10	1,20 - 5,30	1,20 - 6,00	1,39 - 6,07	1,70 - 7,70
Power consumption (min./nom./max.)	kW	❄️	0,19/0,54/ 0,79	0,25/0,86/ 1,12	0,34/1,35/ 1,72	0,35/1,42/ 2,00	0,36/1,99/ 2,20	0,38/2,35/ 2,55
Energy efficiency SEER		❄️	8,60	8,60	7,80	7,30	7,30	6,30
Energy efficiency class		❄️	A+++	A+++	A++	A++	A++	A++
Heating capacity	kW	🔥	3,20	4,20	5,50	6,00	7,00	8,00
Heating range (min.-max.)	kW	🔥	0,90 - 4,80	1,00 - 5,30	1,10 - 6,50	1,10 - 6,50	1,15 - 7,50	1,70 - 8,80
Power consumption (min./nom./max.)	kW	🔥	0,16/0,70/ 1,23	0,20/1,08/ 1,55	0,24/1,48/ 1,90	0,25/1,59/ 1,75	0,26/2,00/ 2,10	0,29/2,35/ 2,75
Energy efficiency SCOP		🔥	5,10	5,10	4,60	4,60	4,60	4,10
Energy efficiency class		🔥	A+++	A+++	A+++	A+++	A+++	A+++

INDOOR UNIT			RAS-B10P2KVS-G-E	RAS-B13P2KVS-G-E	RAS-B16P2KVS-G-E	RAS-B18P2KVS-G-E	RAS-B22P2KVS-G-E	RAS-B24P2KVS-G-E
Sound pressure level (low/med/high)	dB(A)	❄️	19/-/41	19/-/43	22/-/44	26/-/44	27/-/46	28/-/47
Dimensions (HxWxD)	mm		293 x 800x 226	293 x 800x 226	293 x 800x 226	320 x 1053 x 245	320 x 1053 x 245	320 x 1053 x 245

RAS-B05P2KVS-G-E available for multi-split application

OUTDOOR UNIT			RAS-10P2AVS-G-E	RAS-13P2AVS-G-E	RAS-16P2AVS-G-E	RAS-18P2AVS-G-E	RAS-22P2AVS-G-E	RAS-24P2AVS-G-E
Sound pressure level (low/med/high)	dB(A)	❄️	--/--/44	--/--/47	--/--/49	--/--/49	--/--/50	--/--/52
Dimensions (HxWxD)	mm		550 x 780 x 290	630 x 800 x 300				

ACCESSORIES	DESCRIPTION	INCLUDED
Remote control	Infrared remote control included	✓
RB-RXS33-E	Infrared remote control including weekly timer and 8°C frost protection function	

SHORAI CURVE Black



- › Perfect aesthetics & new functionality in the HIGH LINE class
- › High efficiency: energy class A+++ / Clean air: Dust filter & plasma ionizer
- › App control: WiFi module integrated as standard
- › Transparent power consumption: Energy monitoring for single and multi-split systems
- › Definable SILENT function makes submission of official documents & deployment easier



SHORAI
Curve

INDOOR UNIT OUTDOOR UNIT			RAS-B10P2KVS-G-E RAS-10P2AVS-G-E	RAS-B13P2KVS-G-E RAS-13P2AVS-G-E	RAS-B16P2KVS-G-E RAS-16P2AVS-G-E	RAS-B18P2KVS-G-E RAS-18P2AVS-G-E	RAS-B22P2KVS-G-E RAS-22P2AVS-G-E	RAS-B24P2KVS-G-E RAS-24P2AVS-G-E
Cooling capacity	kW	❄️	2,50	3,50	4,60	5,00	6,10	7,00
Cooling range (min.-max.)	kW	❄️	0,89 - 3,20	1,00 - 4,10	1,20 - 5,30	1,20 - 6,00	1,39 - 6,07	1,70 - 7,70
Power consumption (min./nom./max.)	kW	❄️	0,19/0,54/ 0,79	0,25/0,86/ 1,12	0,34/1,35/ 1,72	0,35/1,42/ 2,00	0,36/1,99/ 2,20	0,38/2,35/ 2,55
Energy efficiency SEER		❄️	8,60	8,60	7,80	7,30	7,30	6,30
Energy efficiency class		❄️	A+++	A+++	A++	A++	A++	A++
Heating capacity	kW	🔥	3,20	4,20	5,50	6,00	7,00	8,00
Heating range (min.-max.)	kW	🔥	0,90 - 4,80	1,00 - 5,30	1,10 - 6,50	1,10 - 6,50	1,15 - 7,50	1,70 - 8,80
Power consumption (min./nom./max.)	kW	🔥	0,16/0,70/ 1,23	0,20/1,08/ 1,55	0,24/1,48/ 1,90	0,25/1,59/ 1,75	0,26/2,00/ 2,10	0,29/2,35/ 2,75
Energy efficiency SCOP		🔥	5,10	5,10	4,60	4,60	4,60	4,10
Energy efficiency class		🔥	A+++	A+++	A+++	A+++	A+++	A+++

INDOOR UNIT			RAS-B10P2KVS-G-E	RAS-B13P2KVS-G-E	RAS-B16P2KVS-G-E	RAS-B18P2KVS-G-E	RAS-B22P2KVS-G-E	RAS-B24P2KVS-G-E
Sound pressure level (low/med/high)	dB(A)	❄️	19/-/41	19/-/43	22/-/44	26/-/44	27/-/46	28/-/47
Dimensions (HxWxD)	mm		293 x 800x 226	293 x 800x 226	293 x 800x 226	320 x 1053 x 245	320 x 1053 x 245	320 x 1053 x 245

OUTDOOR UNIT			RAS-10P2AVS-G-E	RAS-13P2AVS-G-E	RAS-16P2AVS-G-E	RAS-18P2AVS-G-E	RAS-22P2AVS-G-E	RAS-24P2AVS-G-E
Sound pressure level (low/med/high)	dB(A)	❄️	--/--/44	--/--/47	--/--/49	--/--/49	--/--/50	--/--/52
Dimensions (HxWxD)	mm		550 x 780 x 290	630 x 800 x 300				

ACCESSORIES	DESCRIPTION	INCLUDED
Remote control	Infrared remote control included	✓
RB-RXS33-E	Infrared remote control including weekly timer and 8°C frost protection function	